REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.						
1. REPORT D	ATE	2. REPORT T Viewgraphs	YPE	3. DATES COV	ERED	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Polarization Properties of Chiral-Core Planar Waveguides				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
Dr. Warren N. Herman				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER		
Naval Air Warfare Center Aircraft Division 22347 Cedar Point Road, Unit #6 Patuxent River, Maryland 20670-1161						
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT						
Approved for public release; distribution is unlimited.						
13. SUPPLEMENTARY NOTES						
· · · · · · · · · · · · · · · · · · ·						
14. ABSTRACT						
A new form for the modal eigenvalue equations of chiral-core planar waveguides provides insight into the transition, with increasing chirality, from TE/TM (transverse electric/magnetic) modes in the archiral case to nearly right-handed and left-handed circularly polarized modes. Dramatic variation of the polarization eccentricity with thickness and frequency is discussed.						
, ,						
15. SUBJECT TERMS						
Polymers; Chiral; waveguides						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Dr. Warren Herman	
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code) (301) 342-9114	
		Unclassified		6	(301) 342-9114 Standard Form 208 (Page 8 08)	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18

## Polarization properties of chiral-core planar waveguides

Presenter: Warren N. Herman

Address: US Navy, NAWCAD

EO Sensors Division AIR456 Patuxent River, MD 20670

### Abstract

A new form for the modal eigenvalue equations of chiral-core planar waveguides provides insight into the transition, with increasing chirality, from TE/TM (transverse electric/magnetic) modes in the achiral case to nearly right-handed and left-handed circularly polarized modes. Dramatic variation of the polarization eccentricity with thickness and frequency is discussed.





# Polarization Properties of Chiral Core Planar Waveguides

#### W.N. Herman

U.S. Navy, NAWCAD

EO Sensors Division, Patuxent River, MD

OTF2001 15-17 October 2001





## **Chiral Core Optical Waveguides**

Top cladding

n<sub>s</sub>
Bottom cladding

#### ISOTROPIC CHIRAL MEDIUM

**Constitutive Relations** (Drude-Born-Federov)

$$\vec{D} = \varepsilon(\vec{E} + \gamma \nabla \times \vec{E}) \qquad \vec{B} = \mu(\vec{H} + \gamma \nabla \times \vec{H})$$

Bohren's Decomposition

$$\vec{E} = \frac{1}{2}(\vec{F}^* + \vec{F}^-) \qquad \vec{H} = \frac{1}{2i}\sqrt{\frac{\varepsilon}{\mu}}(\vec{F}^* - \vec{F}^-)$$

Wave Equation

$$\nabla^2 \vec{F}^{\pm} + (k_0 n_{\pm})^2 \vec{F}^{\pm} = 0$$

Eigenmodes in bulk material circularly polarized

$$\vec{F}^{\pm} = \vec{E}_0 e^{i(k_0 n_{\pm} z - \omega t)} (\hat{x} \pm i\hat{y})$$

Refractive indices for RH and LH waves

$$n_{\pm} = \frac{n_g}{1 \pm \delta}$$
  $\delta = k_0 n_g \gamma$   $n_g = \sqrt{\frac{\varepsilon}{\varepsilon_0}}$   $k_0 = \frac{2\pi}{\lambda}$ 

**Rotatory Power** 

$$\rho = \frac{\pi(n_- - n_+)}{\lambda} \approx k_0 n_g \delta$$

A. Lahlakia, V.K. Varadan, and V.V. Varadan, Time-Harmonic Electromagnetic Fields in Chiral Media, Lecture Notes in Physics Series 335 (Springer-Verlag, Berlin, 1989).

I.V. Lindell, A.H. Sihvola, S.A. Tretyakov, A.J. Viitanen, Electromagnetic Waves in Chiral and Bi-isotropic Media, (Artech House, Norwood, MA, 1994).

#### Modes in Chiral Asymmetric Waveguide

W. N. Herman, accepted J. Opt. Soc. Am. A

$$\vec{F}^{\pm}(y,z) = \vec{\Psi}^{\pm}(y) \exp(-ik_0 n_{eff} z)$$

$$y = 0$$

$$y = 0$$

$$n_g \cdot \gamma z \rightarrow 0$$

$$y = -d$$

Modal equations: (3 equations to be solved simultaneously for  $n_{eff}$ , g, h)

$$u^{\pm}d = \cot^{-1}\left(\sigma_{0}^{\pm} \frac{r_{0} \pm g}{1 \pm g}\right) + \cot^{-1}\left(\sigma_{s}^{\pm} \frac{r_{s} \pm h}{1 \pm h}\right) + m^{\pm}\pi$$

$$h(g, n_{eff}) = \frac{(Sr_{0}^{+} - Sr_{0}^{-}) + (S_{0}^{+} + S_{0}^{-})g}{(Sr_{0}^{+} + Sr_{0}^{-}) + (S_{0}^{+} - S_{0}^{-})g}$$

$$Sr_{0}^{\pm} \equiv r_{0}\sigma_{0}^{\pm} \sin(u^{\pm}d) - \cos(u^{\pm}d)$$

$$Sr_{0}^{\pm} \equiv r_{0}\sigma_{0}^{\pm} \sin(u^{\pm}d) - \cos(u^{\pm}d)$$

$$Sr_{0}^{t} = r_{0}\sigma_{0}^{t} \sin(u^{t}d)$$

$$\sigma_{0}^{t} = (1 \pm \delta)\frac{u^{t}}{v}, \quad \sigma_{s}^{t} = (1 \pm \delta)\frac{u^{t}}{w}, \quad r_{0} = \frac{n_{0}^{2}}{n_{g}^{2}}, \quad r_{s} = \frac{n_{s}^{2}}{n_{g}^{2}}$$

$$u^{t} = k_{0}\sqrt{n_{t}^{2} - n_{cf}^{2}}, \quad v = k_{0}\sqrt{n_{cf}^{2} - n_{0}^{2}}, \quad w = k_{0}\sqrt{n_{cf}^{2} - n_{s}^{2}}$$

$$n^{t} = \frac{n_{g}}{1 \pm \delta}$$

Parameters g, h determine eccentricity of polarization ellipse for transverse E-field:

$$\frac{E_y}{E_x}\bigg|_{v \ge 0} = i \frac{n_{eff}}{n_g} \frac{1}{g} \qquad \qquad \frac{E_y}{E_x}\bigg|_{v \le -d} = i \frac{n_{eff}}{n_g} \frac{1}{h}$$













